

**Lug Kits; Wall and Ceiling Mounting Brackets; Sound Levels**

*New!* **Primary Mechanical Lug Kits**

**Call LynTec — 800-724-4047  
for contractor pricing.**

LynTec Part Number  
Ships with Transformer

Catalog No.	\$ Price Per Kit	Lugs Per Kit	Wire Range	Cap Screws	Current Range
<b>LKP-100</b> 7400DASKP100		3	1/0–14 STR.	1/4 x 1 in	Up to 100 A
<b>LKP-250</b> 7400DASKP250		3	350 kcmil–6 STR.	1/4 x 1 in	101 to 250 A
7400DASKP400		3	600 kcmil–4 STR. (2) 250 kcmil–1/0 STR.	1/4 x 1 3/4 in	201 to 400 A
7400DASKP600		6	600 kcmil–4 STR. (2) 250 kcmil–1/0 STR.	1/4 x 1 3/4 in	601 to 800 A
7400DASKP1000		9	600 kcmil–2 STR.	3/8 x 2 in	601 to 800 A
7400DASKP1200		12	600 kcmil–2 STR.	3/8 x 2 in	801 to 1200 A

*New!* **Secondary Mechanical Lug Kits**

LynTec Part Number  
Ships with Transformer

Catalog No.	\$ Price Per Kit	Lugs Per Kit	Wire Range	Cap Screws	Current Range	Bonding Lugs per Kit	Wire Range
<b>LKS-100</b> 7400DASKS100		5	1/0–14 STR.	1/4 x 1 in	Up to 100 A	1	2–14 STR.
<b>LKS-250</b> 7400DASKS250		5	350 kcmil–6 STR.	1/4 x 1 in	101 to 250 A	1	2–14 STR.
7400DASKS400		5	600 kcmil–4 STR. (2) 250 kcmil–1/0 STR.	1/4 x 1 3/4 in	201 to 400 A	1	1/0–14 STR.
7400DASKS600		10	600 kcmil–2 STR.	1/4 x 1 3/4 in	601 to 800 A	1	250 kcmil–6 STR.
7400DASKS1000		15	600 kcmil–2 STR.	3/8 x 2 in	601 to 800 A	1	250 kcmil–6 STR.
7400DASKS1200		20	600 kcmil–2 STR.	3/8 x 2 in	801 to 1200 A	1	250 kcmil–6 STR.
7400DASKS2000		25	600 kcmil–2 STR.	3/8 x 2 in	1201 to 2000 A	1	350 kcmil–6 STR.

**Weathershields, Wall and Ceiling Mounting Brackets**

Weathershields		Wall Mounting Brackets ♦	
Catalog No.	\$ Price	Catalog No.	\$ Price
WS363		WMB361362	
WS364		WMB363364	
WS370A			★
WS380			
WS381		CMB363	
		CMB364	
		CMB380	
		CMB381	

♦ Wall mounting brackets may be prohibited in some California areas requiring 12-inch spacing from wall.  
★ Base Channels are supplied for ceiling mounting—trapeze hangers must be furnished by user.  
Note: Lugs are not supplied with transformer units. They must be purchased separately.

**Sound Levels**

kVA	NEMA Standard Sound Level
0–9	40 dB
10–50	45 dB
51–150	50 dB
151–300	55 dB
301–500	60 dB
501–700	62 dB
701–1000	64 dB

Note: Square D transformers meet NEMA standards for sound level.  
Lower sound levels are available at an additional charge.

[www.LynTec.com](http://www.LynTec.com)

800-724-4047

8-5 M-F Central time